



Designation	LED Damp Proof Luminaire
Article No	<b>4325050P12040NN</b>
Housing	Aluminum
Colour	White
Optical Cover	Polycarbonate
Reflector	White
Beam Angle	120°
Installation	Direct Mounting
Installation Notes	Through-wirable
Operating Temperature	-20° - + 50°
Intelligent Control	None
Protection against	Water, Dust, Shock
Index of Protection	Schutzart
Protection Class	Schutzklasse
Impact of Resistance	Schlagfestigkeitsgrad
Certificates	Zertifikate
Length	Länge
Width	Breite
Height	Höhe
Weight	Gewicht
Light Source	Lichtquelle
LED Typology	LED Typologie
LED Quantity	LED Anzahl
Wattage	Lampenleistung
Luminous Flux	Lampenlichtstrom
Luminous Efficacy	Lichtausbeute
Light Colour Temperature	Lichtfarbe
Colour Rendering Index	Farbwiedergabeindex
Life Span	Nutzlebensdauer
Power Supply	Betriebsgerät
Input Voltage	Eingangsspannung
Frequency	Frequenz
Power Factor	Leistungsfaktor
Dimming Technology	Dimmtechnik

Bezeichnung	LED Feuchtraumleuchte
Artikel Nr	<b>4325050P12040NN</b>
Gehäuse	Aluminium
Farbe	Weiß
Optische Abdeckung	Polycarbonat
Reflektor	Weiß
Lichtaustrittswinkel	120°
Befestigung	Direktmontage
Installationshinweise	Durchverdrahtung möglich
Betriebstemperatur	-20° - + 50°
Steuerungstechnik	Keine
Schutz vor	Wasser, Staub, Schlag
IP65	
II	
IK10	
CE, RoHS	
1200 mm	
85 mm	
74 mm	
2,07 Kg	
LED	
Epistar SMD2835	
364	
50 W	
6500 lm	
130 lm/W	
4000 K	
Ra > 80	
50000 h	
Lifud	
100 - 277V	
50 / 60 Hz	
>0.90	
nein / none	